

JC010023/WH

Fireguard Next Generation Tilt Downlight

Fireguard Next Generation Mains Twist and Lock Unlamped Downlight Tilt IP20 White



Features & Benefits

- Slim profile, die-cast aluminium bezels
- Designed specifically for LED lamps
- Ultra fast press fit loop-in/loop-out terminal
- Tested for use in fire-rated ceilings
- 15° Tiltable inner bezel
- Complies with 2014 building regulations: Part B, C and E



CLASS I



RATING



NOT SUPPLIED



2yr

WARRANTY

General Information

Product Group

Product Range

Trade Name

Product Shape

Mounting

Product Weight

Color Finish

Overall Dimensions

Recommended Product Location

Minimum Void Requirement

Method Of Fix

Product Aperture Size

IP Rating

Environment

Suitable For Zones

Lamp Supplied

Diffuser / Shade Dimensions (mm)

Fire-rated downlights

Fireguard® Next Generation

Fireguard®

Round

Recessed

0.264kg

White

115.45 x 100mm

indoor use only

150mm

Spring clips

85mm

IP20

Indoor

Outside Zone 2

No

100

Distance From Lighted Object

0.3m

Duration of Fire protection (Mins)

Tested for use in fire-rated ceilings. Full information and up-to-date fire testing certificates for ceiling system types are available on JCC.CO.UK

Origin of manufacturer

Made in China

Warranty

2 year standard warranty (See Website for terms and conditions)

Lighting Product Type 1

Fired Rated Downlights

Electrical

Voltage Rating

220-240

Operating Frequency Hz

50/60Hz

Luminaire Circuit Wattage

7W LED Max

Class

Class I, earth required

Input Electrical Connections

Live(Brown)Neutral(blue)Earth(yellow/green) - Loop in/Loop out press fit terminal

Dimmable

Check with lamp manufacturer

Lampholder

GU10 cap

Thermals

Room Ambient Temperature

25°C

Insulation Coverage

see instruction sheet

Minimum Void Requirement

150mm

Performance Data

Energy Rating

This luminaire is compatible with bulbs of the energy class A+ to E

Construction

Rim Or Attachment

Die-cast aluminium

Packaging

Product Packaged Weight

0.30kg

Quantity Per Outer Carton

20

Outer carton(L)- cm

54

Outer carton(W)- cm

23.5

Outer carton(H)- cm

23.5

Outer carton overall dimensions

54.5 x 23.5 x 23.5cm

Outer carton Net weight- kg

6.01kg

Outer carton Gross weight- kg

6.81kg

Product Bar Code EAN-13 Number

5052544105838

Outer carton Bar Code ITF-14 Number

15052544105835

Standards & Approvals

Manufactured In Accordance To

CE Marked

Date code/Purchase order No.

WEEE Symbol

Certificate Of Conformity

Accredited Members

BS EN 60598-2-1, 2-2



Yes




Yes

yes

Available on request

LIA, ISO9001:2015, ISO14001:2015





JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 21 [20 Aug 2020]