

JC71835/90

Toughbay High Output 200W - Dimmable - 90°-140LPCW - CRI80



Features & Benefits

- Ultra efficient, 140 lumens per circuit Watt
- \bullet High CRI of 80, ensuring a true representation of colour
- Suitable for a wide range of operating temperatures, -30° to +60°
- Step dimming available with remote control (see p.341)
- Suitable for relative humidity levels of up to 90%
- 1-10V dimmable as standard

General Information

Product Group	Toughbay™
Product Range	Circular
Trade Name	Toughbay
Light Source	LED
Light Source Features	Crisp White
Lighting Product Type	Ceiling Mount
Product Shape	Round

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS

Mounting	Surface Mounted
Product Weight	5.2kg
Color Finish	Black
Overall Dimensions	Ø321 x 329mm
Recommended Product Location	Retail and mezzanine applications
Method Of Fix	Suspension eye
IP Rating	IP65
Environment	Indoor
Suitable For Zones	Zone 1
Origin Of Manufacture	Made in China
Guarantee	7 year warranty(inc 2 year on site)
Dimming Protocol Compatibility	1-10V
Mounting Height	7 m for 150-200 lux: Please note this is to be used as a rough guide and does not replace the need for a lighting design
Driver Manufacturer	Philips Xitanium
LED Manufacturer/Type	Philips Lumileds 3030

Electrical

A Cable	Yes
Voltage Rating	220-240
Secondary Running Current	1.05Amp
Primary Running Current	1.06Amp
Operating Frequency (Hz)	50/60Hz
CC or CV	СС
Luminaire Circuit Wattage	200W
Class	Class 1, must be earthed
Output Voltage (V)	100-210VDC
Total Harmonic Distortion (THD)%	<10%

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS

Power Factor Correction	0.95 @ 230V~
Input Electrical Connections	live(brown) neutral(blue) earth(yellow/green)
Dimmable	Yes

Thermals

Max Luminaire Ambient Temp.	50°C
Max Driver/Ballast Ambient Temp.	from -30°C to 60°C
Thermal Cut Out	Yes(auto restart)

Performance Data

Energy Rating	A+
Actual Lumen Output	28000
Lumens Per Circuit Watt	140 LpcW
LED Life (Hours)	54000
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	5700K
Light Distribution Detail	90-degree
Photometry Available	Yes

Construction

Primary Material	Aluminum
Lens	Polycarbonate
Heat Sink	Aluminium
Driver Housing	Aluminium

Packaging

Luminaire Carton Dimensions	106.5 x 38.5 x 28.2cm
Quantity Per Outer Carton	1

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS

Bar Code EAN Number	5052544081408
Packaged Weight	4.4kg

Standards & Approvals

Listings	CE
Manufactured In Accordance To	BS 60598-2-5
CE Marked	Yes
Batch Coded	Yes
WEEE Symbol	yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS

